



# SLC LED DRIVER DALI DT8 CC MULTI TW 50W

DALI DT8 Dimmable LED driver for Tunable White luminaries

Technical data	
Product ID	S32077
DALI version	DALI
DALI Type	DT8
Number of DALI-address	1
DALI DT8 Color Management Protocol	Tc
CE	Yes
Exterior color	White
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
RoHs	Yes
Tc	85 °C
Protection class	II
Housing	Plastic housing
Degree of protection (IP)	IP20
Suitable for constant current	Yes
Dimming DALI	Yes
Dimming method	Pulse Width Modulation (PWM)
Dimming interface	DALI DT8
Input	
Power factor	0.9
Frequency range	[50,60] Hz
Input voltage	[200,240] V
Output	
Output current	250 - 1500 mA
Output power	50 - 50 W
DIP-switch	Yes
Output type	Constant current (CC)
Max total output power	50 W
Output current per channel	[250,1500] A
Tunable White	Yes



17.01.2020

Subject to changes and printing errors

<b>Number of LED Output Channels</b>	2
<b>Output voltage</b>	8 - 48 V
<b>Max output current</b>	1.5 A
<b>Installation</b>	
<b>Length</b>	210 mm
<b>Height</b>	32 mm
<b>Width</b>	50 mm
<b>Model</b>	Static
<b>logistics data</b>	
<b>Brand</b>	SLC
<b>Imported by</b>	The Light Group
<b>General data</b>	
<b>GTIN</b>	7070938057448