

Power supply PushDim



50W PushDim

- 50W power supply with built-in PWM-dimmer
- PushDim
- Mono
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

Output: Constant Voltage(CV)
Input voltage: 100 - 240VAC
Output voltage: 24VDC
Output power: 50W
Output current: 2,08A
IP-grade: IP20
Operating temperature: -20°C ~ +45°C
Dimensions: L:210 W:50 H:32 mm



100W PushDim

- 100W power supply with built-in PWM-dimmer
- PushDim
- Mono
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

Output: Constant Voltage(CV)
Input voltage: 100 - 240VAC
Output voltage: 4x24VDC
Output power: 1x100W / 2x50W / 3x33W / 4x25W
Output current: 1x4,2A / 2x2,1A / 3x1,4A / 4x1,05A
IP-grade: IP20
Operating temperature: -20°C ~ +45°C
Dimensions: L:244 W:64 H:32 mm

Art.no.	Product	Dimensions:
S32004	Power supply CV PushDim 50W	L:210 W:50 H:32 mm
S32006	Power supply CV PushDim 100W	L:244 W:64 H:32 mm

Wiring diagram page 80

Power Supply Phase-Cut Dim



50W Phase-Cut Dim

- 50W power supply with built-in PWM-dimmer
- Dimmable with Phasedim / Trailing edge
- Mono
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

Output: Constant Voltage(CV)
Input voltage: 220 - 240VAC
Output voltage: 24VDC
Output power: 50W
Output current: 2,08A
IP-grade: IP20
Operating temperature: -20°C ~ +45°C
Dimensions: L:184 W:61 H:32 mm



100W Phase-Cut Dim

- 100W Power supply with built-in PWM-dimmer
- Dimmable with Phasedim / Trailing edge
- Mono
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

Output: Constant Voltage(CV)
Input voltage: 220 - 240VAC
Output voltage: 24VDC
Output power: 100W
Output current: 4,2A
IP-grade: IP20
Operating temperature: -20°C ~ +45°C
Dimensions: L:210 W:67 H:34 mm

Art.no.	Product	Dimensions:
S32080	Power Supply CV 24V Phase-Cut Dim 50W	L:184 W:61 H:32 mm
S32081	Power Supply CV 24V Phase-Cut Dim 100W	L:210 W:67 H:34 mm

S56001 **Accessories:** Wall dimmer LED universal, Phase-Cut

Wiring diagram page 81