

**Mains electricity**

230 VAC/50 Hz, max 0.15 A

**Standby power**

0.3 W

**Power factor (PF)**

0.6

**Uout**

3–28 V DC

**Cable area**

Connections: 0.5–4.0 mm<sup>2</sup>

**External operating temperature**

-20 to +35 °C

**Dimensions**

46x46x18 mm

**Protection**

Overtemperature software

Short circuit protection

**Radio**

2.4 GHz mesh

Bluetooth®

<10 dBm

**Radio range**

Approx. 10 m indoors

The Plejd mesh technology extends the range by allowing the units to communicate with each other.

**RISK OF INJURY TO PERSON OR PROPERTY**

All work on the appliance must be carried out by an authorized electrician. National laws and regulations must be followed.

**Plejd AB**

Krokslätts Fabriker 27A  
431 37 Mölndal, Sweden


**Compliant to standards**

Hereby, Plejd AB declares that the radio equipment type LED-10 is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: [plejd.com/compliance](http://plejd.com/compliance)

**LED-10**

## INSTALLATION MANUAL



Further information can be found in the Plejd app or at [plejd.com](http://plejd.com)

## NOTE!

During installation the product is non-dimmable. Use the app to configure before use.

### 1 Connect the product

Install the product in the appliance box behind the push button/box lid or secure it with a Mounting clip (MNT-01, not included) on the wall or DIN rail.

When installing in insulated or warm environments or with several dimmers in the same box, the total power is reduced.


Note that the LED load is non-dimmable until the LED-10 is configured. The load is set at low light level, 20 mA, until the product is configured.

Constant current loads (CC) are connected in series. Constant voltage loads (CV) are connected in parallel.

Load (CC)	
150 mA	1-4 W
350 mA	1-9 W
500 mA	1-10 W
700 mA	1-10 W

Load (CV)	
12 V DC	0-8 W
24 V DC	0-10 W

Use only for LED loads (DC).



$t_c$  marks the point with the highest temperature, 85 °C, at a maximum of 35 °C room temperature.

### Control inputs 1 2

Control inputs 1 and 2 can be used for control with:

- push button (preset)
- light switch
- motion sensor (with neutral conductor).


The inputs can also be used to wirelessly control one or more products from Plejd. Additionally, double click on a push button can be used to activate scenes.


### 2 Follow the instructions in the app

Download the Plejd app on the App Store or Google Play.

After supplying power to the unit by following the wiring diagram, use the app to complete the installation. Setup requires Bluetooth® and an internet connection. You do not need any additional equipment to get started. Use the app to easily configure all settings.

### 3 Hand over the Plejd system

Hand over the Plejd system to your customer by writing the system code on the included sticker . You will find the code in the app once you have completed the installation.

Place the sticker in the distribution box and give the welcome folder  to the customer.

### Support

In the event of any technical questions, please contact our customer service: support@plejd.com | +46 (0) 10 203 89 91