



SLC DALI DT6 Wall Panel Touch MCU/SLAVE

21/11/2023

S52034

Product description

DALI master for use without central DALI bus. Can work both as master and slave. Modes: Group, Address, or Broadcast.

DALI master for use without central DALI bus. Can work both as master and slave. Modes: Group, Address, or Broadcast. Remember the last level. 1 channel with up to 4 saws.

Technical data

Model	Static
Operating method	DALI
Programmable	Yes
Surface-mounted	No
DIN-rail mounting	No
Input voltage	100 - 240 Volt
Degree of protection (IP)	IP20
Length	86 Millimetre
Height	29 Millimetre
Tunable White	No
Frequency range (Hz)	50 - 60
Expected lifetime (Hours) (Ta 45°C)	50000
DALI bus output power (mA)	52
DALI Type	DT6
Brand	SLC

Suitable for outdoor use	No
Number of colour channels	1
Housing	Plastic housing
Built-in	Yes
Output voltage	9,5 - 22 Volt
Max. output current	0,052 Ampere
Protection class	II
Width	86 Millimetre
Mono	Yes
RGBW	No
Expected lifetime (Hours) (Ta 25°C)	110000
DALI-bus power consumption (mA)	15
DALI version	DALI2
Control gear	DALI DT6
GTIN	7070938060608





The Light Group

Datasheet

SLC Scandinavian
Lighting Concept

Produced by

The Light Group
