PRODUCT-DETAILS

# 6330.0610.0

# CDCM 640 Cable distribution cabinet with upper section

## General Information

| | |
|---|---|
| Global Commercial Alias | 6330.0610.0 |
| Extended Product Type | CDCM 640 |
| Product ID | 2CGX063300610 |
| EAN | 7331980009169 |
| Catalog Description | CDCM 640 Cable distribution cabinet with upper section |
| Long Description | Cable Distribution Cabinet with 630 A Al-busbar system. 4-wire system. Foundation is included in the cabinet. Cabinet equipped with an upper part for a metering device or similar systems. |

## Circular Value

| | |
|---|---|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| Environmental Information | 2CGC0037 |
| REACH Declaration | 2CGC0049 |
| RoHS Information | 2CGC0043 |

## Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85381000 |
| Country of Origin | Sweden (SE) |

© 2024 ABB. All rights reserved.

Subject to change without notice

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 2CGC0036 |
| Instructions and Manuals | 439041800B |

## Dimensions

| | |
|---|---|
| Product Net Width | 600 mm |
| Product Net Height | 1800 mm |
| Product Net Depth / Length | 220 mm |
| Product Net Weight | 66 kg |

## Technical

| | |
|---|---|
| Conventional Thermal Current ($I_{the}$) | 630 A |
| Rated Insulation Voltage ($U_i$) | 1000 V |
| Rated Operational Voltage | 400 V |
| Rated Peak Withstand Current Low Voltage ($I_{pk}$) | 55 kA |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | for 1 s 23 kiloampere rms |
| Rated Conditional Short-Circuit Current ($I_{nc}$) | (3//250 A fuse, 400 V) 50 kiloampere rms<br>(3//250 A fuse, 400 V) 3315AFuse400V;85 kiloampere rms |
| Standards | IEC 60439-1,-5 |
| Color | Natural colour |
| Mounting Type | Ground mounted |
| Number of Poles | 4 |
| Degree of Protection | acc. to IEC 60529 IP34D |
| Enclosure Material | Steel |
| Lock Type | Subscriber (CDC-LA) & SE (CDC-LSE) |

## Environmental

| | |
|---|---|
| Environmental Information | 2CGC0037 |

## Certificates and Declarations

| | |
|---|---|
| Declaration of Conformity - CE | 2CGC0022 |
| REACH Declaration | 2CGC0049 |

## Container Information

| | |
|---|---|
| Package Level 1 Units | euro pallet 1 piece |
| Package Level 1 Width | 600 mm |
| Package Level 1 Depth / Length | 1800 mm |
| Package Level 1 Height | 220 mm |
| Package Level 1 Gross Weight | 66 kg |

© 2024 ABB. All rights reserved.

| | |
|---|---|
| Package Level 1 EAN | 7331980009169 |
| Package Level 2 Units | 4 euro pallet |

## Classifications

| | |
|---|---|
| ETIM 7 | EC003517 - Cable distribution cabinet |
| ETIM 8 | EC003517 - Cable distribution cabinet |
| ETIM 9 | EC003517 - Cable distribution cabinet |
| eClass | V11.1 : 27142430 |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |
| E-Number (Finland) | 5451614 |
| E-Number (Sweden) | 0732265 |

## Categories

Low Voltage Products and Systems → Cable Distribution Cabinets → Kabeldon Cable Distribution Cabinets → Cable Distribution Cabinets with Components

© 2024 ABB. All rights reserved.