

PRODUCT-DETAILS

## 3GAA082311-ASE

### IE2 High Efficiency Aluminum Motors, 0.55 kW, 400 V (3GAA082311-ASE)



#### General Information

Product ID	3GAA082311-ASE
ABB Type Designation	M3AA 80A 4
Catalog Description	IE2 High Efficiency Aluminum Motors, 0.55 kW, 400 V (3GAA082311-ASE)

#### Ordering

ABB Type Designation	M3AA 80A 4
Invoice Description	M3AA 80A 4
Product Name	3-Phase squirrel cage motor
Product Type	3AA2_M3AA_IE2_AA
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Selling Unit of Measure	piece
Country of Origin	China (CN)
Customs Tariff Number	85015100
Stocked At (Warehouses)	Menden, Germany Sant Quirze del Vallés - BCN, Spain Shanghai, China Vittuone, Italy
Medium Description	0.55kW, 4 Poles, Frame Size 80, 3 Phases, 400V, 50Hz, IP55 Enclosure,

## IMB3/IM1001 Mounting (3GAA082311-ASE)

Short Description	0.55kW, 4P, Frame Size 80, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
-------------------	---

## Electrical

### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.55 kW	1406 r/min	1.29 A	0.780	77.10 %	3.73 N·m	5.40
D	--	50 Hz	230 V	0.55 kW	1406 r/min	2.24 A	0.780	77.10 %	3.73 N·m	5.40
Y	--	60 Hz	460 V	0.55 kW	1721 r/min	1.15 A	0.740	75.50 %	3.05 N·m	6.50

Connection Configuration	Y
Temperature Class Default	--
Input Voltage (U <sub>in</sub> )	400 V
Frequency (f)	50 Hz
Output Power	0.55 kW
Altitude	1000 m
Ambient Temperature	40 °C
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 77.1 % Partial Load (75%) 78.6 % Partial Load (50%) 76.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 75.5 % Partial Load (75%) 75.6 % Partial Load (50%) 72.2 %
IP Class	IP55
Insulation Class	ICLF
Direction of Rotation	Both sides
Number of Poles (High)	4
Two Speed Motor	No
Type of Duty	S1
Voltage Code	S

## Mechanical

Frame Material	Aluminum
Frame Size	80
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Lubrication	For life
IM Class	IMB3 IM1001
Terminator Box Location	Top

## Dimensions

Package Level 1 Units	0 carton
Product Net Depth / Length	292.5 mm

Product Net Height	193.5 mm
Product Net Width	154 mm
Product Net Weight	9.6 kg
Gross Weight	12.6 kg

---

## Environmental

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
SCIP	27ac6190-e1ce-4080-8654-6552aaabbe58 Finland (FI)

---

## Classifications

Standards	IEC 60034-1
UNSPSC	26101100

---

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Process Performance Motors → IE2 High Efficiency Aluminum Motors

