

## Junistar Soft Black 740lm 2700K Ra 98 Trailing edge dimming / Linect

Article code: 903213  
 EAN: 7021989032137




### Electrical

Wattage: 9W  
 System wattage: 11W  
 Voltage: 220-240V  
 Frequency (Hz): 50/60Hz  
 Max. luminaires per circuit breaker: B10: 77, B16: 123, C10: 77, C16: 123

### Light technic

Type of light source: LED  
 Luminous flux: 740lm  
 Efficacy: 67 lm/W  
 Colour temperature: 2700K  
 Colour rendering (CRI): Ra 98  
 MacAdams factor: SDCM: 2  
 Lifetime: L90/B10>100,000  
 Light distribution: Direct  
 Optic: Reflector  
 Beam angle: 42°  
 UGR: UGR<19



### Control/Dimming

Type: Trailing edge dimming / Linect

### Protection

Luminaire class: Class II SELV

### Energy and approvals

Contains light source of energy class: F  
 Breeam: Fulfil Hea 01 for flicker free lighting  
 BVB: Yes

### Materials and finish

Housing: Aluminium  
 Colour: Black (RAL 9004)  
 Optics: Tempered glass

### Mounting/Connection

Mounting: Recessed, Indoor / Outdoor  
 Connection: 3 pol Linect / screwless terminal block

### Dimensions

Height (mm) H: 53  
 Diameter (mm) D: 94  
 Cut-out (mm): 83  
 Ceiling void depth (mm): 51  
 Distance to flammable materials: 10mm  
 Weight (kg) gross/net: 0.696 / 0.58

### Packaging

Packing dimensions (mm): 110 x 110 x 110

