



EN ISO 20345:2022



RESOLUTE  
**FORZA HIGH**  
**BOA®**

45477-09L

**S7S FO HI \*CI SC HRO SR**

**Size:** 36-48  
**Weight:** 670 gr.

**Fit:** 11

**Working Environment:**  
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



**FEATURES**

**UPPER**

Full Grain leather Hydro 1,8-2,0 mm  
Mesh H.T. no ladder

**LINING**

3D Green Air 320 gr.

**ANTISLIP LINING**

DUALMICRO

**INSOLE**

QRS02 Green

**TOE CAP**

Fiber cap SXT

**RESISTANCE TO PERFORATION**

KX Antiperforation recycled PS

**TYPE**

Ankle boot

**SOLE**

**PU-RUBBER VIBRAM ECOSTEP PRO-HRO-SR**

Sole with anti-wear scaffap. Outsole in VIBRAM RECYCLED (≥30%) rubber, resistant to 300° C by contact (HRO), to oils. Design with self-cleaning outsole, with SR Antislip standard.

**Boa® lace length**  
L+1 - 115cm


**TECHNOLOGIES**

**Removable Insole**



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

**Protection elements**



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

**Lateral stability**



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

**Torsional stability**



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.





**PU - RUBBER**

SOLE 45



**SLIP RESISTANCE**

EN ISO 20344:2021

**BASIC**  
CERAMIC WITH NAILS

FORWARD HEEL SLIP ≥ 0.31	<b>0,45</b>	
BACKWARD FOREPART SLIP ≥ 0.36	<b>0,47</b>	

**SR**  
CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP ≥ 0.19	<b>0,28</b>	
BACKWARD FOREPART SLIP ≥ 0.22	<b>0,25</b>	

**Electrical features**



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

**Other**



The HDry membrane is hydrophilic with high perspiration capacity. It guarantees high performance and durability, facilitating the maintenance of ideal conditions and comfort for the user.

