



EN ISO 20345:2022



RESOLUTE
FORZA BOA
45460-15L

S7S FO HI *CI SC HRO SR

Size: 36-48
Weight: 660 gr.

Fit: 11

Working Environment:
Multipurpose, Logistics and Light Industry, Components and Automotive



FEATURES

UPPER

Mesh H.T. no ladder
Full Grain leather Hydro 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

KX Antiperforation recycled PS

TYPE

Low Shoe

SOLE

PU-RUBBER VIBRAM ECOSTEP PRO-HRO-SR

Sole with anti-wear scaff cap. Outsole in VIBRAM RECYCLED ($\geq 30\%$) rubber, resistant to 300° C by contact (HRO), to oils. Design with self-cleaning outsole, with SR Antislip standard.

Boa® lace length
L6 - 85cm


TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use

Protection elements



Composite toe cap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable

Lateral stability



Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

Torsional stability



Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.






PU - RUBBER

SOLE 45

SLIP RESISTANCE

EN ISO 20344:2021

	FORWARD HEEL SLIP ≥ 0.31	0,45	
BASIC CERAMIC WITH NAILS	BACKWARD FOREPART SLIP ≥ 0.36	0,47	
SR CERAMIC WITH GLYCERINE	FORWARD HEEL SLIP ≥ 0.19	0,28	
	BACKWARD FOREPART SLIP ≥ 0.22	0,25	



Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.



Other

D30 PROGRESSIVE CUSHIONING AND ADAPTIVE STABILITY

D30 materials are made using a combination of advanced polymer chemistry and cutting-edge science. It absorbs and dissipates energy during and impact, with superior stability, cushioning and anti-fatigue effect.

