

Screen wire connector brassfor screen wires or concentric conductors up to 70 mm².

No.	Width across flats	Torque (Nm)	Shear bolts	Diameter D1 Ø d1 (mm)	Diameter D2 Ø d2 (mm)	Dimension L L (mm)	Packing unit
332 511 009	SW 4	7	-	6.7	12	40	25
332 513 009	SW 4	7	■	10.5	16	40	25

No.	Al ○ (mm ²)	Al ● (mm ²)	Al ◆ (mm ²)	Cu ○ (mm ²)	Cu ● (mm ²)	Cu ◆ (mm ²)
332 511 009	4 - 16	4 - 16	-	4 - 16	4 - 16	-
332 513 009	4 - 10	10 - 70	10 - 70	4 - 10	10 - 70	10 - 70

Screen wire connector brass Al

- For VDE and TGL cables
- Tinned
- With blind hole



No.	Width across flats	Torque (Nm)	Shear bolts	Diameter D1 Ø d1 (mm)	Diameter D2 Ø d2 (mm)	Dimension L L (mm)	Packing unit
332 513 005	SW 5	10	-	20	11	55	25

No.	Cu ● (mm ²)	flat conductor cross section
332 513 005	16 - 50	3 - 13 pieces flat 1 x 5.2 Al