

Delivery contents

With gauge ring and screw cap, optional with fuse insert;
outgoing sliding gasket optional for one cable or two; optional
with screws for light pole connection M6 x 12 mm; different
ground conductors in 10 mm²; casing cover optional in clear
or black; the box can be delivered preassembled in a single
cardboard box

Technical data

Nominal voltage / -current	400 V / 16 A
Degree of protection	IP54
Protection class	II
Fuses	2 x D01 (E14) up to 16 A
Measurements (L x W x H)	340 x 84 x 72 mm (HSW 2520); 340 x 84 x 79 mm (HSW 2525); 340 x 84 x 92 mm (HSW 2529)

	from 89 mm (HSW 2520); from 95 mm (HSW 2525); from 106 mm (HSW 2529)
Pole internal diameter	
	from 85 x 350 mm
Door size	

Connection cross-sections

	for 3 cables 5x 6 mm ² up to 5 x 16 mm ²
Input connectors	

	for 2 cables 4/5 x 1,5 mm ² up to 4/5 x 2,5 mm ²
Output connectors	



REG.-Nr. 122009

If you have any further questions, do not hesitate to contact us

+49 (2192) 9166-0

✉ info@hsw-stadtfeld.de

[\(mailto:info@hsw-stadtfeld.de\)](mailto:info@hsw-stadtfeld.de)

[Homepage](#)
([en/homepage/](#))

[About us](#)
([en/company/](#))

[Contact](#) ([en/contact/](#))

[Sitemap](#)
([/seitenverzeichnis/](#))

[Imprint](#) ([en/imprint/](#))

[Products:](#)
([/produkte/](#))

[Cable fuse boxes](#)
([en/products/cable-fuse-boxes/](#))

[Pole mount socket](#)
([en/products/neue-mastanbausteckdosen-holder-en-gb/](#))

[Ripple control receiver](#)
([en/products/ripple-control-receiver/](#))

[LED solutions](#)
([en/products/led-solutions/](#))

[Lamp holder](#)
([en/products/lamp-holder/](#))

[Porcelain terminal block](#) ([en/products/porcelain-terminal-block/](#))

HSW Stadtfeld

Bevertalstr. 20, D-42499 Hückeswagen



([en/contact/](#))

Search on hsw-stadtfeld.de:

hsw-stadtfeld.de

[Imprint](#)
([en/imprint/](#))

[Privacy](#) ([en/data-protection/](#))

[Business Terms](#) ([en/general-terms-and-conditions-of-business/](#))

Copyright
2017