

Busbar system with accessories

Busbar supports



KSST 36
Support for 400 A and 630 A busbars. Fixing hole pitch 85 mm. To split busbar systems for metering with current transformers, etc.



KSST 316, 316/23, 316/100
Support for 400 A, 630 A, 1000 A and 1600 A busbars. Primarily in enclosures type SDC.



KSST-CDC
Support for 400 and 630 A busbars when mounting in enclosure type CDC. The kit consists of a complete support and two fixing bolts.



KSST 36-CDC
Support for 400 A and 630 A phase bars. Fixing hole pitch is 85 mm. Used in split and shortened busbar systems in CDC enclosures.



KLKB-S 630, 1200
Bar bridge to interconnect busbar systems in two enclosures. May only be installed on dead busbar.

Designation	ID No.	Rated current	Free space behind the bars	Number of modules	Suitable enclosures	Weight
		A	mm	M *		kg/each
KSST 36	2CGX0 53320186	–	11	2	all	0.1
KSST 316	2CGX0 53320104	–	9	2	all	0.5
KSST 316/23	2CGX0 53320106	–	23	2	all	0.8
KSST 316/100	2CGX0 53320105	–	100	2	SDC	1.1
KSST-CDC	2CGX0 53320231	–	15	–	CDC	0.4
KSST 36-CDC	2CGX0 53320187	–	15	2	CDC	0.3
KLKB-S 630	2CGX0 51190106	630	–	–	all	3.4
KLKB-S 1200	2CGX0 51190107	1200	–	–	SDC	6.6

* One module M = 12.5 mm.